Printing date 16.05.2014

Version number 2

I Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SUNCLEAR
- · Article number: 227530
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against --
- · Application of the substance / the mixture Clear coating material, Varnish
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Car Paint Warehouse Unit 9,

Aspen Close Kembrey Park,

Kembrey Trade Centre

Swindon SN2 8AJ

Tel: +44 (0)1793 535192

- · Further information obtainable from: QHSE Department
- · 1.4 Emergency telephone number:

Tel: +44 (0)1793 535192 (08.00 / 17.00)

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam, Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H3.36 . . . May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.

Xi; Sensitising

May cause sensitisation by skin contact.

F+; *Extremely flammable*

R12: Extremely flammable.

R52/53-66: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurized container.

(Contd. on page 2)

SUNOX

Printing date 16.05.2014

Version number 2

Trade name: SUNCLEAR

(Contd. of page 1)

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





CHSUS

GHSO

- · Signal word Danger
- · Hazard-determining components of labelling:

aliphatic polycyanate

n-butyl acetate

 $\label{lem:mixture} \begin{tabular}{ll} Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly (oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly (oxyethylene) \\ \begin{tabular}{ll} Alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly (oxyethylene) \\ \end{tabular}$

Decandicarbonsäure

bis(1,2,2,6,6-pentamethyl-4-piperidinyl)ester

isobutyl methacrylate

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains isocyanates. May produce an allergic reaction.

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- $\cdot \textbf{\textit{Description:}} \ \textit{Mixture of substances listed below with nonhazardous additions.}$

(Contd. on page 3)

SUNOX

Printing date 16.05.2014

Version number 2

Trade name: SUNCLEAR

Dangerous components:	(0	Contd. of pag
CAS: 115-10-6	dimethyl ether	25-<509
EINECS: 204-065-8	F + R12	23-<307
Reg.nr.: 01-2119472128-37		
CAS: 123-86-4	n-butyl acetate	20-<259
EINECS: 204-658-1	R10-66-67	20 120 /
Reg.nr.: 01-2119485493-29	🕟 🚯 Flam. Liq. 3, H226; 🕦 STOT SE 3, H336	
CAS: 1330-20-7	xylene, mixture of isomers	12.5-<20
EINECS: 215-535-7	X Xn R20/21; X Xi R38	
Reg.nr.: 01-2119488216-32		
	♠ Flam. Liq. 3, H226; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 28182-81-2	aliphatic polycyanate	2.5-<5.0
Reg.nr.: 01-2119485796-17	LIMI IMI IMI	
G1 G 100 11 1	♦ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	2.5.5.0
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene	2.5-<5.0
Reg.nr.: 02-2119752523-40	Xn R20; → F R11 → Flam. Liq. 2, H225; → Acute Tox. 4, H332	
CAS: 110-12-3	5-methylhexan-2-one	<2.5%
EINECS: 203-737-8	<i>Xn R20 Xn R20</i>	\2. 3 /0
200, 200 707 0	R10	
	🏇 Flam. Liq. 3, H226; ♦♦ Acute Tox. 4, H332	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	<2.5%
EINECS: 265-199-0	X Xn R65; X Xi R37; ₹ N R51/53	
	R10-66-67	
	♠ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♠ STOT SE 3, H335-H336	
CAS: 108-10-1	4-methylpentan-2-one	<2.5%
EINECS: 203-550-1	🗶 Xn R20; 🗶 Xi R36/37; 🐞 F R11	
	R66	
	♠ Flam. Liq. 2, H225; ♠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 95-63-6	1,2,4-trimethylbenzene	<2.5%
EINECS: 202-436-9	Xn R20; Xi R36/37/38; N R51/53	\2. 370
202 100)	R10	
	Flam. Liq. 3, H226; 🍫 Aquatic Chronic 2, H411; 🗘 Acute	
	Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3,	
	H335	
CAS: 53880-05-0	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate,	<1.0%
NLP: 500-125-5	oligomers X N R42/43	
ELINCS: 400-830-7	Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-	≤0.5%
ELINCS. 400-030-7	hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and	<u> 5</u> 0.5 /0
	alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)	
	propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-	
	hydroxyphenyl)propionyloxypoly(oxyethylene)	
	Xi R43; N R51/53	
	🕸 Aquatic Chronic 2, H411; 🕚 Skin Sens. 1, H317	Contd. on pag

GB

SUNOX

Printing date 16.05.2014

Version number 2

Trade name: SUNCLEAR

G1 G 100 (5 0		ontd. of pa
CAS: 108-67-8 EINECS: 203-604-4	mesitylene Xi R37; № N R51/53 R10 Flam. Liq. 3, H226; Aquatic Chronic 2, H411; STOT SE 3, H335	≤0.5%
CAS: 103-65-1 EINECS: 203-132-9	propylbenzene Xn R65; Xi R37; N R51/53 R10 → Flam. Liq. 3, H226; → Asp. Tox. 1, H304; → Aquatic Chronic 2, H411; → STOT SE 3, H335	≤0.5%
CAS: 61788-93-0 EINECS: 263-020-0	Amines, coco alkyldimethyl ☐ C R34; Xn R22; N R50 ♦ Skin Corr. IB, H314; ♦ Aquatic Acute 1, H400; ♦ Acute Tox. 4, H302	≤0.5%
CAS: 41556-26-7 EINECS: 255-437-1	Decandicarbonsäure bis(1,2,2,6,6-pentamethyl-4-piperidinyl)ester Xi R43; № N R50/53 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Sens. 1, H317	<u><</u> 0.5%
CAS: 97-86-9 EINECS: 202-613-0	isobutyl methacrylate Xi R36/37/38; Xi R43; № N R50 R10 Flam. Liq. 3, H226; Aquatic Acute 1, H400; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<u>≤</u> 0.5%

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.

For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

 \cdot After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, bluspoeder of waterstraal. Grotere brand met waterstraal of met schuim. Vaten met water afkoelen.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters -

(Contd. on page 5)



Printing date 16.05.2014

Version number 2

Trade name: SUNCLEAR

(Contd. of page 4)

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Protective equipment: Mouth respiratory protective device.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Do not allow product to reach sewage system or any water course.

· 6.3 Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 2B
- · 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

T 1		. •		•			
· Ingredients	with lin	ut values	S THAT	reautre	monitoring	at the	workniace:
11151 000001000	,, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	in received	,	·······		cor crec	" or represent

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 6)

GB

SUNOX

Printing date 16.05.2014

Version number 2

Trade name: SUNCLEAR

(Contd. of page 5) 1330-20-7 xylene, mixture of isomers WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV 100-41-4 ethylbenzene WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm 110-12-3 5-methylhexan-2-one WEL Short-term value: 475 mg/m³, 100 ppm Long-term value: 95 mg/m³, 20 ppm 108-10-1 4-methylpentan-2-one WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sk, BMGV 95-63-6 1,2,4-trimethylbenzene WEL Long-term value: 125 mg/m³, 25 ppm ILV· Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid 108-10-1 4-methylpentan-2-one BMGV 20 µmol/L Medium: urine Sampling time: post shift

- Parameter: 4-methylpentan-2-one

 · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.

Otherwise, filter class A / P2 or self contained.

· Protection of hands:



Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 7)

SUNOX

Printing date 16.05.2014 Version number 2

Trade name: SUNCLEAR

(Contd. of page 6)

· Material of gloves Natural rubber, NR Butyl rubber, BR

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

· Eye protection: Safety glasses

· 9.1 Information	on hasic	nhysical and	chemical	nronerties
2.1 IIIIVIIIIUUUU	on vasic	pnysicai ana	Chemicai	DIODELLES

· General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gaseous): Not applicable.

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

• Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

 Lower:
 1.1 Vol %

 Upper:
 18.6 Vol %

· Vapour pressure at 20 °C: 5200 hPa

Density at 20 °C:
 Relative density
 Vapour density
 Evaporation rate
 0.83 g/cm³
 Not determined.
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.
Kinematic: Not determined.

· Solvent content:

VOC-(EU) ---

675.7 g/l

• 9.2 Other information No further relevant information available.

CI



Printing date 16.05.2014

Version number 2

Trade name: SUNCLEAR

(Contd. of page 7)

10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

7	D/I C5	n walne	rolovan	+ for	alaggifi.	antion.

1330-20-7 xylene, mixture of isomers

 Oral
 LD50
 8700 mg/kg (rat)

 Dermal
 LD50
 >2000 mg/kg (rabbit)

Inhalative LC50/4 h 6350 mg/l (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

OralLD503592 mg/kg (rat) (ECD-Prüfrichtlinie401)DermalLD50>3160 mg/kg (rab) (OECD-Prüfrichtlinie 402)

Inhalative LC50/4 h > 10.2 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

Vapours have narcotic effect.

12 Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

		_		
1330-20-7	xvlene.	mixture	of isomers	ď

EC50 (24h) >175 mg/l (bacteria)

EC50 / 48h | 3.82 mg/l (daphnia magna / Wasserfloh)

EC50/72h 4.7 mg/l (Pseudokirchneriella subcapitata)

LC50/96h 7.6 mg/l (oncorhynchus mykiss / Regenbogenforelle)

64742-95-6 Solvent naphtha (petroleum), light arom.

EC50 / 48h | >100 mg/l (daphnia magna / Wasserfloh)

EC50/96h 19 mg/l (desmdesmus subspicatus / Grünalge) (OECD - Prüfrichtlinie 201)

LC50/96h >100 mg/l (Regenbogenforelle) (67/548/EWG Annex 5 C.1.)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 9)

SUNOX

Printing date 16.05.2014

Version number 2

Trade name: SUNCLEAR

(Contd. of page 8)

- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 04 metallic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

7 4 '	7 N		C .
12	I ran	'nort in	formation
		טוט טוטעו	

	1	11	I/N_Numh	
--	---	----	----------	--

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class 2 5F Gases.

· Label 2.

· IMDG, IATA



· Class
 · Label
 2.1
 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

(Contd. on page 10)

SUNOX

Printing date 16.05.2014

Trade name: SUNCLEAR

Version number 2

	(Contd. of p	page 9
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
· 14.6 Special precautions for user	Warning: Gases.	
Danger code (Kemler):	-	
· EMS Number:	F- D , S - U	
· 14.7 Transport in bulk according to Anno	ex II of	
MARPOL73/78 and the IBC Code	Not applicable.	
· Transport/Additional information:		
· <i>ADR</i>		
· Limited quantities (LQ)	1L	
· Transport category	2	
· Tunnel restriction code	D	
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1	

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

•	Rel	levant	phrases
---	-----	--------	---------

H220	Extremely	flammable	gas.

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- *H400 Very toxic to aquatic life.*
- *H410* Very toxic to aquatic life with long lasting effects.
- *H411 Toxic to aquatic life with long lasting effects.*
- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R22 Harmful if swallowed.
- R34 Causes burns.
- R36/37 Irritating to eyes and respiratory system.
- R36/37/38 Irritating to eyes, respiratory system and skin.

(Contd. on page 11)

SUNOX

Printing date 16.05.2014

Version number 2

Trade name: SUNCLEAR

(Contd. of page 10)

R37 Irritating to respiratory system.

R38 Irritating to skin.

R42/43 May cause sensitisation by inhalation and skin contact.

R43 May cause sensitisation by skin contact.

R50 Very toxic to aquatic organisms.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmfull: may cause lung damage if swallowed

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· Contact: Anwendungstechnik

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

GB