

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2014 Version number 1 Revision: 13.05.2014

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SUNWELD ZINC WELD SPRAY 500 ML
- · Article number: SUNWELD
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Preparation
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Car Paint Warehouse, Unit 9,

Aspen Close Kembrey Park,

Kembrey Trade Centre, Swindon, SN2 8AJ

Tel: +44 (0)1793 535192 | Email: info@sunox.co.uk

- · Further information obtainable from: QHSE Department
- · 1.4 Emergency telephone number:

Tel: +44 (0)1793 535192 (08.00 / 17.00)

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36: Irritating to eyes.



F+; Extremely flammable

R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurized container.

GB

SUNOX

Printing date 13.05.2014

Version number 1

Trade name: SUNWELD ZINC WELD SPRAY 500 ML

(Contd. of page 1)

Has a narcotizing effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

acetone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

· Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8	acetone	25-50%		
Reg.nr.: 01-2119471330-49-xxxx	R66-67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336			
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether F+ R12 Flam. Gas 1, H220; Flam. Liq. 1, H224 Press. Gas, H280	12.5-20%		

(Contd. on page 3)

SUNOX

Printing date 13.05.2014

Version number 1

Trade name: SUNWELD ZINC WELD SPRAY 500 ML

CAS: 74-98-6	propane	Contd. of pag 5-10%
EINECS: 200-827-9	F + R12	
Index number: 601-003-00-5	♠ Flam. Gas 1, H220	. –
Reg.nr.: 01-2119486944-21-xxxx	Press. Gas, H280	
CAS: 123-86-4	n-butyl acetate	5-10%
EINECS: 204-658-1	R10-66-67	
Index number: 607-025-00-1	♠ Flam. Liq. 3, H226	
Reg.nr.: 01-2119485493-29-xxxx	♦ STOT SE 3, H336	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	5-10%
EINECS: 203-603-9	R10	
Index number: 607-195-00-7	🚸 Flam. Liq. 3, H226	
Reg.nr.: 01-2119475791-29-xxxx		
CAS: 106-97-8	butane	5-10%
EINECS: 203-448-7	F+ R12	
Index number: 601-004-00-0	© Flam. Gas 1, H220	
8		- 100
CAS: 7429-90-5	aluminium powder (stabilized)	5-10%
EINECS: 231-072-3	FR11	
Index number: 013-002-00-1 Reg.nr.: 01-2119529243-45-xxxx	ô Flam. Sol. 1, H228	
CAS: 75-28-5	: l	5-10%
EINECS: 200-857-2	isobutane F+ R12	3-10%
Index number: 601-004-00-0	♠ Flam. Gas 1, H220	- =
Reg.nr.: 01-2119485395-27-xxxx		
CAS: 1330-20-7	xvlene	1-2.59
EINECS: 215-535-7	xytene xn R20/21	1 2.37
Index number: 601-022-00-9	Xi R38	
Reg.nr.: 01-2119488216-32	RIO	
-	♠ Flam. Liq. 3, H226	-
	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 9004-70-0	Nitrocellulose (nitrogen content <12.6%)	1-2.5%
	▶ F R11	
	♠ Flam. Sol. 1, H228	

4 First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.05.2014

Version number 1



Trade name: SUNWELD ZINC WELD SPRAY 500 ML

(Contd. of page 3)

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

67-64-1 ace	etone	
	term value: 3620 mg/m³, 1500 ppm term value: 1210 mg/m³, 500 ppm	
115-10-6 di	imethyl ether	
	t-term value: 958 mg/m³, 500 ppm -term value: 766 mg/m³, 400 ppm	
123-86-4 n	-butyl acetate	

(Contd. on page 5)

SUNOX

Printing date 13.05.2014

Version number 1

Trade name: SUNWELD ZINC WELD SPRAY 500 ML

(Contd. of page 4)

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · **Protection of hands:** Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

(Contd. on page 6)

- GB

SUNOX

Printing date 13.05.2014

Version number 1

Trade name: SUNWELD ZINC WELD SPRAY 500 ML

	(Contd. of page
Flash point:	<0 °C (<32 °F) Not applicable, as aerosol.
Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits: Lower: Upper:	2.6 Vol % 26.2 Vol %
Vapour pressure at 20 °C (68 °F):	4000 hPa (3000 mm Hg)
Density at 20°C (68°F): Relative density Vapour density Evaporation rate	0.758 g/cm³ (6.326 lbs/gal) Not determined. Not determined. Not applicable.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Solvent content: Organic solvents: EU-VOC: EU-VOC in %:	89.6 % 679.3 g/l 89.61 %
Solids content: 9.2 Other information	10.4 % No further relevant information available.

10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:				
67-64-1 a	cetone			
Oral	LD50	5800 mg/kg (rat)		
Dermal	LD50	20000 mg/kg (rabbit)		

(Contd. on page 7)

SUNOX

Printing date 13.05.2014

Version number 1

Trade name: SUNWELD ZINC WELD SPRAY 500 ML

		(Contd. of page 6)			
Inhalative	LC50 / 4 h	39 mg/m3 (rat)			
115-10-6 d	115-10-6 dimethyl ether				
Inhalative	LC50 / 4 h	308 mg/m3 (rat)			
123-86-4 n	-butyl aceta	nte			
Oral	LD50	10770 mg/kg (rat)			
Dermal	LD50	>17600 mg/kg (rabbit)			
Inhalative	LC50 / 4 h	>21.0 mg/m3 (rat)			
108-65-6 2	108-65-6 2-methoxy-1-methylethyl acetate				
Oral	LD50	8532 mg/kg (rat)			
Dermal	LD50	>5000 mg/kg (rabbit)			
Inhalative	LC50 / 4 h	35.7 mg/m3 (rat)			
106-97-8 b	106-97-8 butane				
Inhalative	LC50 / 4 h	658000 mg/m3 (rat)			
1330-20-7	1330-20-7 xylene				
Oral	LD50	4300 mg/kg (rat)			
Dermal	LD50	2000 mg/kg (rabbit)			
	LC50 / 4 h	22.1 mg/m3 (rat)			

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

· 12.1 Toxicity

8800 mg/l (daphnia magna)
2262 mg/l (daphnia magna)
5540 mg/l (fish)
ther
>4000 mg/l (daphnia magna)
etate
44 mg/l (daphnia magna)
320 mg/l (algae)
205 mg/l (daphnia magna)
18 mg/l (Pimephales promelas)
2-1-methylethyl acetate
408 mg/l (daphnia magna)
7.4 mg/l (daphnia magna)
13.5 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

SUNOX

Printing date 13.05.2014

Version number 1

Trade name: SUNWELD ZINC WELD SPRAY 500 ML

(Contd. of page 7)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

•	European	waste	catal	logue
---	----------	-------	-------	-------

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 04 metallic packaging

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

14.1 UN-Number	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
ADR	1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
Class	2 5F Gases.
Label	2.1
· IMDG, IATA	
· Class	2.1
· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
· Marine pollutant:	No

(Contd. on page 9)

SUNOX

Printing date 13.05.2014

Version number 1

Trade name: SUNWELD ZINC WELD SPRAY 500 ML

		(Contd. of page 8
· EMS Number:	F-D,S-U	
· 14.7 Transport in bulk according to Ann MARPOL73/78 and the IBC Code	nex II of Not applicable.	
Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	1L	
Transport category	2	
Tunnel restriction code	D	
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1	

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H220 Extremely flammable gas.
- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H280 Contains gas under pressure; may explode if heated.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20/21 Harmful by inhalation and in contact with skin.
- R36 Irritating to eyes.
- R38 Irritating to skin.
- R66 Repeated exposure may cause skin dryness or cracking.
- *R67* Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: QHSE Department
- · Contact: QHSE Department
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2014

Version number 1

Trade name: SUNWELD ZINC WELD SPRAY 500 ML

(Contd. of page 9)

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Flam. Liq. 1: Flammable liquids, Hazard Category 1

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 2: Hammable liquids, Hazard Category 3
Flam. Sol. 1: Flammable solids, Hazard Category 1
Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· * Data compared to the previous version altered.